

#187 Hole-Type Brick Veneer Anchor

SECTION 04 00 00 MASONRY
Section 04 05 19.16 Masonry Anchors
Section 04 05 23 Masonry Accessories

PART 1: GENERAL

1.1 RELATED SECTIONS

A. Provide shop drawings for all product locations.

1.2 SUBMITTALS

A. Manufacturer Certificate of Compliance for materials.

B. Product Data: Manufacturer's data sheet on each type of product furnished.

PART 2: MANUFACTURER

2.1 MANUFACTURER

Heckmann Building Products
110 Richards Ave.
Norwalk, CT 06854-1685
800-621-4140
Email: info@heckmannanchors.com
Website: www.heckmannanchors.com

2.2 APPLICATIONS

- A. Provide anchoring systems that comply with TMS 402/602-22 Building Code Requirements and Specification for Masonry Structures 2022.
- B. ASTM A1008/A1008M-24 Sheet Metal Anchors and Ties (Plain Steel).
- C. ASTM A153/A153M-16a Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware.
- D. Stainless Steel AISI **[Type 304] or [Type 316]**.
 - 1) ASTM A240/A240M-24b Standard Specification for Chromium and Chromium Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications.

- 2) ASTM A666/666M-24 Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar.
- 3) ASTM A276/A276M-24a Standard Specification for Stainless Steel Bars and Shapes.

2.3 MATERIALS

Select the Following

187 HOLE-TYPE BRICK VENEER ANCHOR

Standard: 16 gauge x 1-1/4" wide with a 1-1/2" od bend with a centered 5/16" diameter hole. **Length:** [3-1/2"] [5-1/2"]

Steel Type: [Type 304 Stainless Steel] [Hotdip Galvanized After Fabrication]

Custom: (For custom sizes refer to product 340-A Corrugated L-Anchor with Hole)

PART 3: EXECUTION

- A. Install as specified in applicable masonry section(s).