

## #352 Rubber Expansion Joint

### SECTION 04 00 00 MASONRY

#### Section 04 05 23 Masonry Accessories

#### Section 04 05 23.13 Masonry Control and Expansion Joints

#### Section 04 21 13.13 Brick Veneer Masonry

## **PART 1: GENERAL**

### 1.1 RELATED SECTIONS

- A. Provide shop drawings for all product locations.

### 1.2 SUBMITTALS

- A. Manufacturer Certificate of Compliance for materials.
- B. Product Data: Manufacturer's data sheet on each type of product furnished.

## **PART 2: MANUFACTURER**

### 2.1 MANUFACTURER

Acceptable Manufacturer:  
Heckmann Building Products  
110 Richards Ave.  
Norwalk, CT 06854-1685  
800-621-4140  
Email: [info@heckmannanchors.com](mailto:info@heckmannanchors.com)  
Website: [www.heckmannanchors.com](http://www.heckmannanchors.com)

### 2.2 APPLICATIONS

- A. Provide anchoring systems that comply with TMS 402/602-22 Building Code Requirements and Specification for Masonry Structures 2022.
- B. ASTM D2000-18 Standard Classification System for Rubber Products in Automotive Applications
- C. ASTM D2240-15e1 Standard Test Method for Rubber Property Durometer Hardness

### 2.3 MATERIALS

## **No. 352 RUBBER CONTROL JOINT**

Standard: Thickness: 1/4" Depth: [2-5/8"] [6-7/8'] [11-1/8"]  
Tee: Thickness: 1/4" Depth 2-5/8"

Materials: Extruded Rubber

### **PART 3: EXECUTION**

- A. Install as specified in applicable masonry section(s).
- B. Install vertically at expansion joints and seal interior and exterior joint with backer rod and sealant.