

#394 Corrugated Column Anchor with Square Hole

SECTION 04 00 00 MASONRY
Section 04 05 19.16 Masonry Anchors
Section 05 12 00 Structural Steel Framing

PART 1: GENERAL

1.1 RELATED SECTIONS

A. Provide shop drawings for all product locations.

1.2 SUBMITTALS

A. Manufacturer Certificate of Compliance for materials.

B. Product Data: Manufacturer's data sheet on each type of product furnished.

PART 2: MANUFACTURER

2.1 MANUFACTURER

Acceptable Manufacturer:
Heckmann Building Products
110 Richards Ave.
Norwalk, CT 06854-1685
800-621-4140
Email: info@heckmannanchors.com
Website: www.heckmannanchors.com

2.2 APPLICATIONS

- A. Stainless Steel AISI Type 304.
- 1) ASTM A240/A240M-24b Standard Specification for Chromium and Chromium Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications.
 - 2) ASTM A666/666M-24 Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar.
 - 3) ASTM A276/A276M-24a Standard Specification for Stainless Steel Bars and Shapes.
- B. ASTM B69-13 Zinc Alloy 710 for use as a firewall anchor (1/8" thick only).

2.3 MATERIALS

NO. 394 CORRUGATED COLUMN ANCHOR WITH SQUARE HOLE

[gage [3/16][1/8]] x [3-1/4" wide] x [overall length]

[Sliding bar starts 1" from end – bar size [1/2"] [3/4"] [1"]]

Materials: [Type 304 Stainless Steel] [Zinc Alloy 710 Firewall 1/8" only]

PART 3: EXECUTION

A. Install as specified in applicable masonry section(s).