#84 WEEP-THRU MORTAR DEFLECTOR

SECTION 042000 UNIT MASONRY Section 04 05 23 Masonry Accessories

PART 1: GENERAL

1.1 RELATED SECTIONS

A. Section 07 25 00 - WeatherBarriers

1.2 SUBMITTALS

- A. Manufacturer Certificate of Compliance for materials.
- B. Product Data: Manufacturer's data sheet on each type of product furnished.

PART 2: MANUFACTURER

2.1 MANUFACTURER

Heckmann Building Products 110 Richards Ave. Norwalk, CT 06854-1685 800-621-4140

Email: info@heckmannanchors.com
Website: www.heckmannanchors.com

2.2 APPLICATIONS

A. Provide anchoring systems that comply with TMS 402/602-22 Building Code Requirements and Specification for Masonry Structures 2022.

2.3 MATERIALS

Open mesh to collect and prevent mortar droppings from clogging weep vents. Select Size: [#84-5 - 1/2" thick] [#84-1 1" thick] [#84-2 - 2" thick]

PART 3: EXECUTION

- A. Install as specified in applicable masonry section(s).
 - a. Extend flashing at least 6" above the top of the Weep-Thru Mortar Deflector.

- b. Remove all mortar droppings at the bottom of the cavity before installing the Weep-Thru Mortar Deflector.
- c. Install a continuous row of the Weep-Thru Mortar Deflector in the cavity at the base directly on the flashing with the dovetail facing upward.

END OF SECTION