

Rubble Stone Anchors
#398-C L-Type Rubble Clips
#398-J J-Hook Rod
#398 Rubble Stone Wire Tie

SECTION 04 00 00 MASONRY
Section 04 05 19.16 Masonry Anchors
Section 04 05 19.29 Stone Anchors

PART 1: GENERAL

1.1 RELATED SECTIONS

- A. Provide shop drawings for all product locations.

1.2 SUBMITTALS

- A. Manufacturer Certificate of Compliance for materials.
- B. Product Data: Manufacturer's data sheet on each type of product furnished.

PART 2: MANUFACTURER

2.1 MANUFACTURER

Acceptable Manufacturer:
Heckmann Building Products
110 Richards Ave.
Norwalk, CT 06854-1685
800-621-4140
Email: info@heckmannanchors.com
Website: www.heckmannanchors.com

2.2 APPLICATIONS

- A. Provide anchoring systems that comply with TMS 402/602-22 Building Code Requirements and Specification for Masonry Structures 2022.
 - 1) Stainless Steel AISI Type 304
 - 2) ASTM A240/A240M-24b Standard Specification for Chromium and Chromium Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications.
 - 3) ASTM A666/666M-24 Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar.
 - 4) ASTM A276/A276M-24a Standard Specification for Stainless Steel Bars and Shapes.

5) ASTM A580/A580M-23 Standard Specification for Stainless Steel Wire.

2.3 MATERIALS

A. Products

#398-C L-Type Rubble Clips

12 gauge x 2-3/4" wide x [length (od)] x [bend length (od)] x [centered hole diameter] x horizontal 13/32" x 1-1/4" slot centered [inches] from end.

#398-J J-Hook Rod

[[5/16" diameter] [3/8" diameter] x 52" long

#398 Rubble Stone Wire Tie

[3/16" diameter] x length [3"] [4"] [5"] [6"] [7"] [9"] with welded 3/16" dia crossbar

B. Materials: [Type 304 Stainless Steel]

PART 3: EXECUTION

A. Install as specified in applicable masonry section(s).